

Queues

This chapter presents two ADTs: the Queue and the Priority Queue. In real life, a **queue** is a line of customers waiting for service of some kind. In most cases, the first customer in line is the next customer to be served. There are exceptions, though. At airports, customers whose flights are leaving soon are sometimes taken from the middle of the queue. At supermarkets, a polite customer might let someone with only a few items go first.

The rule that determines who goes next is called the **queueing policy**. The simplest queueing policy is called **FIFO**, for first-in-first-out. The most general queueing policy is **priority queueing**, in which each customer is assigned a priority and the customer with the highest priority goes first, regardless of the order of arrival. We say this is the most general policy because the priority can be based on anything: what time a flight leaves; how many groceries the customer has; or how important the customer is. Of course, not all queueing policies are fair, but fairness is in the eye of the beholder.

The Queue ADT and the Priority Queue ADT have the same set of operations. The difference is in the semantics of the operations: a queue uses the FIFO policy; and a priority queue (as the name suggests) uses the priority queueing policy.

20.1. The Queue ADT

The Queue ADT is defined by the following operations:

`__init__`

Initialize a new empty queue.

`insert`

Add a new item to the queue.

`remove`

Remove and return an item from the queue. The item that is returned is the first one that was added.

`is_empty`

Check whether the queue is empty.

20.2. Linked Queue

The first implementation of the Queue ADT we will look at is called a **linked queue** because it is made up of linked Node objects. Here is the class definition:

```
class Queue:
    def __init__(self):
        self.length = 0
        self.head = None

    def is_empty(self):
        return (self.length == 0)

    def insert(self, cargo):
        node = Node(cargo)
        node.next = None
        if self.head == None:
            # if list is empty the new node goes first
            self.head = node
        else:
            # find the last node in the list
            last = self.head
            while last.next: last = last.next
            # append the new node
            last.next = node
        self.length = self.length + 1

    def remove(self):
        cargo = self.head.cargo
        self.head = self.head.next
        self.length = self.length - 1
        return cargo
```

The methods `is_empty` and `remove` are identical to the `LinkedList` methods `is_empty` and `remove_first`. The `insert` method is new and a bit more complicated.

We want to insert new items at the end of the list. If the queue is empty, we just set `head` to refer to the new node.

Otherwise, we traverse the list to the last node and tack the new node on the end. We can identify the last node because its next attribute is None.

There are two invariants for a properly formed Queue object. The value of length should be the number of nodes in the queue, and the last node should have next equal to None. Convince yourself that this method preserves both invariants.

20.3. Performance characteristics

Normally when we invoke a method, we are not concerned with the details of its implementation. But there is one detail we might want to know—the performance characteristics of the method. How long does it take, and how does the run time change as the number of items in the collection increases?

First look at remove. There are no loops or function calls here, suggesting that the runtime of this method is the same every time. Such a method is called a **constant-time** operation. In reality, the method might be slightly faster when the list is empty since it skips the body of the conditional, but that difference is not significant.

The performance of insert is very different. In the general case, we have to traverse the list to find the last element.

This traversal takes time proportional to the length of the list. Since the runtime is a linear function of the length, this method is called **linear time**. Compared to constant time, that's very bad.

20.4. Improved Linked Queue

We would like an implementation of the Queue ADT that can perform all operations in constant time. One way to do that is to modify the Queue class so that it maintains a reference to both the first and the last node, as shown in the figure:

The ImprovedQueue implementation looks like this:

```
class ImprovedQueue:
    def __init__(self):
        self.length = 0
        self.head = None
        self.last = None

    def is_empty(self):
```

```
return (self.length == 0)
```

So far, the only change is the attribute last. It is used in insert and remove methods:

```
class ImprovedQueue:
    ...
    def insert(self, cargo):
        node = Node(cargo)
        node.next = None
        if self.length == 0:
            # if list is empty, the new node is head and last
            self.head = self.last = node
        else:
            # find the last node
            last = self.last
            # append the new node
            last.next = node
            self.last = node
        self.length = self.length + 1
```

Since last keeps track of the last node, we don't have to search for it. As a result, this method is constant time.

There is a price to pay for that speed. We have to add a special case to remove to set last to None when the last node is removed:

```
class ImprovedQueue:
    ...
    def remove(self):
        cargo = self.head.cargo
        self.head = self.head.next
        self.length = self.length - 1
        if self.length == 0:
            self.last = None
        return cargo
```

This implementation is more complicated than the Linked Queue implementation, and it is more difficult to demonstrate that it is correct. The advantage is that we have achieved the goal – both insert and remove are constant-time operations.

20.5. Priority queue

The Priority Queue ADT has the same interface as the Queue ADT, but different semantics. Again, the interface is:

`__init__`

Initialize a new empty queue.

`insert`

Add a new item to the queue.

`remove`

Remove and return an item from the queue. The item that is returned is the one with the highest priority.

`is_empty`

Check whether the queue is empty.

The semantic difference is that the item that is removed from the queue is not necessarily the first one that was added. Rather, it is the item in the queue that has the highest priority. What the priorities are and how they compare to each other are not specified by the Priority Queue implementation. It depends on which items are in the queue.

For example, if the items in the queue have names, we might choose them in alphabetical order. If they are bowling scores, we might go from highest to lowest, but if they are golf scores, we would go from lowest to highest. As long as we can compare the items in the queue, we can find and remove the one with the highest priority.

This implementation of Priority Queue has as an attribute a Python list that contains the items in the queue.

```
class PriorityQueue:
    def __init__(self):
        self.items = []

    def is_empty(self):
        return self.items == []

    def insert(self, item):
        self.items.append(item)
```

The initialization method, `is_empty`, and `insert` are all veneers on list operations. The only interesting method is `remove`:

```
class PriorityQueue:
    ...
    def remove(self):
        maxi = 0
        for i in range(1, len(self.items)):
            if self.items[i] > self.items[maxi]: maxi = i
        item = self.items[maxi]
        self.items[maxi:maxi+1] = []
        return item
```

At the beginning of each iteration, `maxi` holds the index of the biggest item (highest priority) we have seen *so far*. Each time through the loop, the program compares the item to the champion. If the new item is bigger, the value of `maxi` is set to `i`.

When the `for` statement completes, `maxi` is the index of the biggest item. This item is removed from the list and returned.

Let's test the implementation:

```
>>> q = PriorityQueue()
>>> q.insert(11)
>>> q.insert(12)
>>> q.insert(14)
>>> q.insert(13)
>>> while not q.is_empty(): print q.remove()
14
13
12
11
```

If the queue contains simple numbers or strings, they are removed in numerical or alphabetical order, from highest to lowest. Python can find the biggest integer or string because it can compare them using the built-in comparison operators.

If the queue contains an object type, it has to provide a `__cmp__` method. When `remove` uses the `>` operator to compare items, it invokes the `__cmp__` for one of

the items and passes the other as a parameter. As long as the `__cmp__` method works correctly, the Priority Queue will work.

20.6. The Golfer class

As an example of an object with an unusual definition of priority, let's implement a class called `Golfer` that keeps track of the names and scores of golfers. As usual, we start by defining `__init__` and `__str__`:

```
class Golfer:
    def __init__(self, name, score):
        self.name = name
        self.score = score

    def __str__(self):
        return "%-16s: %d" % (self.name, self.score)
```

`__str__` uses the format operator to put the names and scores in neat columns.

Next we define a version of `__cmp__` where the lowest score gets highest priority. As always, `__cmp__` returns 1 if `self` is greater than `other`, -1 if `self` is less than `other`, and 0 if they are equal.

```
class Golfer:
    ...
    def __cmp__(self, other):
        if self.score < other.score: return 1 # less is more
        if self.score > other.score: return -1
        return 0
```

Now we are ready to test the priority queue with the `Golfer` class:

```
>>> tiger = Golfer("Tiger Woods", 61)
>>> phil = Golfer("Phil Mickelson", 72)
>>> hal = Golfer("Hal Sutton", 69)
>>>
>>> pq = PriorityQueue()
>>> pq.insert(tiger)
>>> pq.insert(phil)
>>> pq.insert(hal)
```

```
>>> while not pq.is_empty(): print pq.remove()
Tiger Woods    : 61
Hal Sutton     : 69
```

```
Phil Mickelson : 72
```

20.7. Glossary

queue

An ordered set of objects waiting for a service of some kind.

Queue

An ADT that performs the operations one might perform on a queue.

queueing policy

The rules that determine which member of a queue is removed next.

FIFO

First In, First Out, a queueing policy in which the first member to arrive is the first to be removed.

priority queue

A queueing policy in which each member has a priority determined by external factors. The member with the highest priority is the first to be removed.

Priority Queue

An ADT that defines the operations one might perform on a priority queue.

linked queue

An implementation of a queue using a linked list.

constant time

An operation whose runtime does not depend on the size of the data structure.

linear time

An operation whose runtime is a linear function of the size of the data structure.

20.8. Exercises

Write an implementation of the Queue ADT using a Python list. Compare the performance of this implementation to the ImprovedQueue for a range of queue lengths. #. Write an implementation of the Priority Queue ADT using a linked list. You

should keep the list sorted so that removal is a constant time operation. Compare the performance of this implementation with the Python list implementation.

Source: <http://openbookproject.net/thinkcs/python/english2e/ch20.html>